

Sanitary cubicle

Type Elegance
Inlay doors

Technical data sheet



- **Panels & doors**
Massive self-supporting panel boards with a base of synthetic resin and cellulose. The core of the panels is made up from phenolic resin finished on both sides with an integrated decorative coating. The homogeneous panels are obtained through compression under high pressure and high temperatures. The panels have a solid construction, without pores, neither at the surface, nor in the core, which makes them anti-microbial, water-, impact- and scratch resistant. Standard fire resistance M2/C-s2,d0 (M1/B-s2,d0 at extra cost).

The panels have a solid surface (FA) and are of 13 mm thick. The composition and the structure of the panel is particularly developed for use within humid conditions.

The doors are mounted in the same plane as the walls. The touching sides of the doors are rebated, therefore providing complete privacy without the need for overlapping doors/panels to cover any sightlines. 4 Silencers are mounted in the door rebates making for a quiet closing of the doors. All sides are rounded off.

ASI ALPACO

Wijtschotbaan 3 - bus1
2900 Schoten - België

Tel. +32 (0)3 360 91 20
Fax. +32 (0)3 360 91 29

E-mail: info@alpaco.be
www.asi-alpaco.com

Sanitary cubicle

Type Elegance Inlay doors

Technical data sheet



- **Dimensions**

The height of the cubicles is 2065 mm (incl. stabilization profile), including 150 mm of free space. The height of the intermediate panel is 1995mm. Other heights are possible on request, at an additional cost.

- **Hardware**

Door-panels are fitted with three hinges, of which one is equipped with an adjustable spring allowing the doors to return always into a closed position. The door fittings consist of 2 nylon doorknobs and 1 revolving knob with a free/occupied indication, which can be opened from the outside in case of emergency. All door fittings are invisibly mounted and are standard made of high-quality nylon (polyamide).

Optional: door hardware in aluminium or stainless steel (extra charge).

- **Pedestals**

The adjustable pedestals are also made from high-quality nylon (polyamide), colored in the mass, Ø35mm with round cover rosette 70mm. They are mounted invisibly.

Optional: legs in aluminum or stainless steel (extra charge).

- **Profiles**

Extruded aluminum profiles, powder coated of about 60 microns thick. The thickness of all aluminum profiles is minimum 2 mm..

- ◇ U-profile for wall mounting: 30x20mm.
- ◇ Round (Ø34mm) aluminum tube profile for stabilization, mounting with special aluminum spacers.
- ◇ Rounded corner profile for freestanding cubicles: 38x38mm.

- **Accessories**

Urinal screens, splash walls and benches in HPL as well as coat hooks, paper roll holders, toilet brushes, etc. (nylon, aluminum or stainless steel) are available at an additional cost.

- **Colors**

- ◇ Solid core panels are available in 15 standard colors according to our color chart. Other colors are possible at a longer delivery time and additional cost.
- ◇ Nylon door fittings, pedestals and accessories available in 7 standard colors according to our color chart.
- ◇ Aluminum profiles available in 7 standard colors according to our color chart as well as clear anodized.

- **Scope of application**

"Elegance" cubicles are allocated for the construction of: toilets, showers and dressings and are often used for : office buildings, schools, swimming pools, sport centers, campsites, hospitals, train stations, industrial halls, etc.

